ERDI LR1200E2

Component datasheet · ERDI TECH LTD · laser rangefinder modules and eye-safe laser sources

Model	**LR1200E2**
Family	905nm
Wavelength	905 ± 5 nm
Measuring range (with the condition it was measured under)	4-1200 m — Standard range; actual reach depends on target and environment.
Accuracy / resolution	±1 m (6 m ≤ D < 500 m); ±(0.5 + 0.001D) m (500 m ≤ D ≤ 1200 m) — Whiteboard target, 90% reflectivity: 2.3 × 2.3 m for the first distance int
Update rate	2-10 Hz (adaptive) — Completed distance outputs; not the optical pulse-repetition rate.
Interface	UART-TTL — Custom configurations are specified separately
Supply	3.3-5 V
Power	≈ 1 W — Approximate value in the specification table
Mass	≤10 g
Dimensions	—
Operating temperature	-20 °C to +55 °C Storage temperature -40 °C to +60 °C Mechanical drawing dimensions 25.7 × 13.3 × 24.6 mm — Drawing nominal values. Observe
Laser class	—
Pulse energy	—

How to read the range figure. A range number without its target size, reflectance and visibility is not comparable to anything. The figure above carries the manufacturer's own condition, quoted verbatim. If you need a different target or a different visibility, ask — the usable range changes, and we would rather state both than let you discover it in the field.

What is not in this sheet. Pinout, command frames and the protocol document are supplied with the units, matched to your firmware revision. We do not publish them here because frames differ between revisions and a generic frame does nothing on your bench.

ERDI TECH LTD · No.23 Chaoyang Road, Xihe Street, Longquanyi District, Chengdu 610107, China · specs@erdilrf.com · https://specs.erdilrf.com · figures transcribed from the manufacturer's published specification