ERDI LRF1200A1

Component datasheet · ERDI TECH LTD · laser rangefinder modules and eye-safe laser sources

Model	**LRF1200A1**
Family	905nm
Wavelength	905 nm
Measuring range (with the condition it was measured under)	5-1200 m — Building target
Accuracy / resolution	±1 m (5 m ≤ L ≤ 100 m); ±(1 + 0.004L) m (L > 100 m) — L is distance in meters.
Update rate	1-3 Hz
Interface	UART, 3.3 V TTL
Supply	3.3 ± 0.1 V DC
Power	≤1.5 W
Mass	18 g
Dimensions	Ø23 × 40 mm — Cylindrical housing; use the model drawing for tolerances.
Operating temperature	-20 °C to +60 °C Storage temperature -55 °C to +65 °C
Laser class	—
Pulse energy	—

How to read the range figure. A range number without its target size, reflectance and visibility is not comparable to anything. The figure above carries the manufacturer's own condition, quoted verbatim. If you need a different target or a different visibility, ask — the usable range changes, and we would rather state both than let you discover it in the field.

What is not in this sheet. Pinout, command frames and the protocol document are supplied with the units, matched to your firmware revision. We do not publish them here because frames differ between revisions and a generic frame does nothing on your bench.