ERDI SPD1200N0

Component datasheet · ERDI TECH LTD · laser rangefinder modules and eye-safe laser sources

Model	**SPD1200N0**
Family	905nm
Wavelength	905 nm ±5 nm Beam divergence <4.5 mrad
Measuring range (with the condition it was measured under)	0.2-1200 m; maximum 1500 m at night — strong sunlight or low visibility may reduce range
Accuracy / resolution	±0.3 m (D ≤100 m); ±0.3 m + D × 0.7‰ (100 m < D <1200 m) Measurement frequency 2-15 Hz or 4-15 Hz, adaptive — both alternatives appear in th
Update rate	—
Interface	UART-TTL (customizable)
Supply	3.3-5 V Operating power Average ≈0.45 W; maximum ≤0.75 W
Power	—
Mass	≈5 g Protection rating IP67 inside lens chamber — Source-stated classification or rating; not independently certified by this page
Dimensions	Diameter 15.7 × 21.3 mm (round, with sealing groove)
Operating temperature	-20°C to +60°C
Laser class	—
Pulse energy	—

How to read the range figure. A range number without its target size, reflectance and visibility is not comparable to anything. The figure above carries the manufacturer's own condition, quoted verbatim. If you need a different target or a different visibility, ask — the usable range changes, and we would rather state both than let you discover it in the field.

What is not in this sheet. Pinout, command frames and the protocol document are supplied with the units, matched to your firmware revision. We do not publish them here because frames differ between revisions and a generic frame does nothing on your bench.