ERDI SPD1200S2

Component datasheet · ERDI TECH LTD · laser rangefinder modules and eye-safe laser sources

Model	**SPD1200S2**
Family	905nm
Wavelength	905nm±5nm
Measuring range (with the condition it was measured under)	Catalog range: 0.2–1,200 m. Sources also report a 1,500 m night-time maximum under special conditions; it is not a guaranteed range.
Accuracy / resolution	±0.3m (≤400m)±0.5m + d × 0.1% (400m＜d＜1,200m)
Update rate	4Hz~15Hz Adaptive
Interface	UART-TTL, Customizable
Supply	3.3V~5V
Power	—
Mass	10 g
Dimensions	Technical tables (current published table, archive
Operating temperature	–20 °C~+60 °C
Laser class	IEC CLASS I
Pulse energy	—

Source note. Figures pending confirmation against the manufacturer's current specification sheet.

How to read the range figure. A range number without its target size, reflectance and visibility is not comparable to anything. The figure above carries the manufacturer's own condition, quoted verbatim. If you need a different target or a different visibility, ask — the usable range changes, and we would rather state both than let you discover it in the field.

What is not in this sheet. Pinout, command frames and the protocol document are supplied with the units, matched to your firmware revision. We do not publish them here because frames differ between revisions and a generic frame does nothing on your bench.