ERDI SPD1200Z2

Component datasheet · ERDI TECH LTD · laser rangefinder modules and eye-safe laser sources

Model	**SPD1200Z2**
Family	905nm
Wavelength	905nm±5nm
Measuring range (with the condition it was measured under)	Catalog range: 0.2–1,200 m; strong sunlight or low visibility may reduce range. Sources also list a 1,500 m night-time maximum under special conditions; it is not a guaranteed range.
Accuracy / resolution	Current published table and archived factory PDF: ±0.2 m (d≤200 m); ±0.5 m (d≤40
Update rate	Current published table and archived factory PDF technical table: 2–20 Hz adapti
Interface	UART-TTL, Customizable
Supply	3.3V~5V
Power	—
Mass	6 g
Dimensions	5.0mm × 7mm
Operating temperature	–20 °C~+60 °C
Laser class	IEC CLASS I
Pulse energy	—

Source note. Figures pending confirmation against the manufacturer's current specification sheet.

How to read the range figure. A range number without its target size, reflectance and visibility is not comparable to anything. The figure above carries the manufacturer's own condition, quoted verbatim. If you need a different target or a different visibility, ask — the usable range changes, and we would rather state both than let you discover it in the field.

What is not in this sheet. Pinout, command frames and the protocol document are supplied with the units, matched to your firmware revision. We do not publish them here because frames differ between revisions and a generic frame does nothing on your bench.